

ET12000



Specifications

Type	R
Generator	
AC frequency	50 Hz
AC output voltage	220V
Rated AC output	Three phase 10,000 VA Single phase 2,700 VA x 3
Maximum AC output	Three phase 11,000 VA Single phase 3,000 VA x 3
DC output	-
Voltage regulation system	AVR
Engine	
Model	GX620K1
Type	Air Cooled, 4-stroke OHV 900, V-Twin
Displacement	614 cm ³
Net Power (SAE J1349)*	13.5kW (18.1 HP)/3600 min-1 rpm
Rated power output	11.8.0kW (15.8 HP)/3600 min-1 rpm
Max. Net Torque (SAE J1349)*	40.5 N.m (4.14 kgf.m, 29.9 lbf.ft)/2500 min-1 rpm
Fuel tank capacity	31 L
Fuel used	Unleaded Gasoline (Oktan 86 or higher)
Ignition system	Transistorized Magneto
Starting system	Electric starter
Continuous operating hour	-
Operating noise level (7m) (Lwa)	- 101 dB
Air cleaner	Dry paper type
Oil capacity	Without oil filter replacement : 1.1 L With oil filter replacement : 1.4 L
Recommended oil	-
Dimensions	
Length	973 mm
Width	552 mm
Height	637 mm
Dry weight (kg)	150 kg
Standard Features	
Eco-Throttle	-
AC circuit breaker	v
DC circuit breaker	-
Oil alert	v
Fuel indicator	v
Voltmeter	v
Parallel operation connection port	-
Parallel operation connection cable	-
i-monitor	-
Remote Control Box	-
Large capacity air cleaner	-
Large capacity fuel tank	-
Large capacity muffler	-
*With eco throttle switch on.	

Vendor:	Willie Melo
Contact:	846383606
Email:	willie.melo@afritool.co.mz