



AFRITOOL (M) LDA.

Av. 25 de Setembro No. 2009 Caixa Postal N°2183, Maputo Moçambique

Tel: +258 21 309 068/328 998 Fax: +258 21 328 997/333 809

e-mail: afritoool@tv cabo.co.mz / afritoool@afritoool.com

Nuit: 400109524

2014 GROM SPECIFICATIONS

Engine Type	124.9cc air-cooled single-cylinder four-stroke
Induction	PGM-FI with automatic enrichment
Ignition	Electronic
Bore and Stroke	52.4mm x 57.9mm
Compression ratio	9.3:1
Valve Train	SOHC; two valves per cylinder

DRIVE TRAIN

Transmission	Four-speed
Final Drive	Chain

CHASSIS /SUSPENSION /BRAKES

Front Suspension	31mm inverted fork; 3.9 inches travel
Rear Suspension	Single shock with steel box-section swingarm; 4.1 inches travel
Front Brake	Single 220mm disc with hydraulic dual-piston caliper
Rear Brake	Single 190mm disc with hydraulic single-piston caliper
Front Tire	120/70-12
Rear Tire	130/70-12

DIMENSIONS

Wheelbase	47.4 inches
Rake (Caster Angle)	25.0°
Trail	81mm (3.2 inches)
Seat Height	29.7 inches
Curb Weight full tank of fuel—ready to ride.)	225 pounds (Includes all standard equipment, required fluids and
Fuel Capacity	1.45 gallons

OTHER

Model ID	Grom125
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ due to emissions equipment.
Available Colors	Pearl Red, Metallic Black

FACTORY WARRANTY INFORMATION

One Year	Unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

*All figures are preliminary and subject to change.
©2013 American Honda Motor Co., Inc. - Motorcycle Division

