## EM10000



## **Product Features**

Honda 4-Stroke engine, OHV, 90° V-Twin, 2 Cylinder GX620 Rated Output 800VA / Max. Output 9000VA Net Weight 150Kg With automatic Voltage Regulator (AVR) Electric starter Sysytem for easier starting Quite operation73dB(A), during 8000 - 9000 W operation

## **Specifications**

Specifications	
Туре	R
Generator	
AC frequency	-
AC output voltage	-
Rated AC output	8000 VA
Maximum AC output	9000 VA
DC output	-
Voltage regulation system	AVR
<u>Engine</u>	
Model	GX620K1
Туре	Air Cooled, 4-stroke OHV 900, V-Twin
Displacement	614 cm3
Net Power (SAE J1349)*	13.5kW (18.1 HP)/3600 min-1 rpm
Rated power output	11.8.0kW (15.8 HP)/3600 min-1 rpm
Max. Net Torque (SAE J1349)*	40.5 N.m (4.14 kgf.m, 29.9 lbf.ft)/2500 min-1
Fuel tank capacity	31 L
Fuel used	Unleaded gasoline (Oktan 86 or higher)
Ignition system	Transistorized Magneto
Starting system	Electric starter
Continuous operating hour	-
Operating noise level (7m)	-
(Lwa)	101 dB
Air cleaner	Dry paper type
Oil capacity	Without oil filter repalcement : 1.1 L
	With oil filter repalcement : 1.4 L
Recommended oil	-
<u>Dimensions</u>	
Length	973 mm
Width	552 mm
Height	637 mm
Dry weight (kg)	150 kg
Standard Features	
Eco-Throttle	-
AC circuit breaker	V
DC circuit breaker	-
Oil alert	V
Fuel indicator	V
Voltmeter	V
Parallel operation connection port	-
Parallel operation connection cable	-
i-monitor	-
Remote Control Box	-
Large capacity air cleaner	-
Large capacity fuel tank	-
Large capacity muffler	-
*With eco throttle switch on.	

Vendidor:	Willie Melo
Contacto:	846383606
Email:	willie.melo@afritool.co.mz