

## AFRITOOL (M) LDA.

Av. 25 de Setembro No. 2009 Caixa Postal N°2183, Maputo Moçambique Tel: +258 21 309 068/328 998 Fax: +258 21 328 997/333 809 e-mail: afritool@tvcabo.co.mz / afritool@afritool.com

SPECIFICATIONS - Honda CTX200 Bushlander			
Engine	Single Cylinder, 4-stroke,	Front	37mm Telescopic Fork, 158mm
	Air cooled, OHC 2 valve	Suspension	Axle Travel
Displacement	197cc	Rear	High Density Rear Shock Tube,
_		Suspension	150mm Axle Travel
Bore & Stroke	63.5 x 62.2mm	Front	Wire spoke (Rim size: 21 x
		Wheels	1.40")
Compression Ratio	9.0:1	Rear	Wire spoke (Rim size: 18 x
		Wheels	1.85")
Max. Power Output	10.6 [14.5] / 7,000rpm	Front Tyre	80/100-21 51R
Max. Torque	15.2 [1.48] / 6,000rpm	Rear Tyre	100/100-18
Carburation	Carburetor	Front	130mm leading/trailing drum
		Brake	
Ignition System	AC-CDI Battery	Rear Brake	110mm leading/ trailing drum
Starter	Electric Start w/ kick	Frame	semi-Double Cradle; Steel
	start back-up		
Final Drive	O-ring Sealed chain	Caster	26.9°
		Angle	
Length x Width x	2,196 x 938 x 1,152 mm	Trail	104mm
Height			
Wheelbase	1,363mm	Kerb	127kg
		Weight	
Seat Height	823mm	Colour	Red
<b>Ground Clearance</b>	238mm		
Fuel Tank Capacity	8.5 litres / 1.8 reserve		







