

## AFRITOOL (M) LDA.

Av. 25 de Setembro No. 2009 Caixa Postal N°2183, Maputo Moçambique Tel: +258 21 309 068/328 998 Fax: +258 21 328 997/333 809 e-mail: afritool@tvcabo.co.mz / afritool@afritool.com

SPECIFICATIONS XL125LEK			
Engine	Air cooled, 4-stroke 2-valve	Front	T31mm Telescopic Fork, 159mm Axle
· ·	OHC single	Suspension	Travel
Displacement	124.7cc	Rear	High Density Rear Shock Tube, 148mm
		Suspension	Axle Travel
Bore & Stroke	52.4 x 57.8mm	Front	Wire spoke (Rim size: 21 x 1.40)
		Wheels	
Compression Ratio	9.2:1	Rear	Wire spoke (Rim size: 18 x 2.15)
		Wheels	
Max. Power Output	8.4 kw/8000rpm	Front Tyre	70/100-21M/C 44P
Max. Torque	10.9Nm/6500rpm	Rear Tyre	100/90-18M/C 56P
Carburation	Carburetor	Front	130mm leading/trailing drum
		Brake	
Ignition System	DC-CDI Battery	Rear Brake	110mm leading/ trailing drum
Starter	Kick-starter	Frame	semi-Double Cradle; Steel
Final Drive	O-ring Sealed chain	Caster	26.9°
		Angle	
Length x Width x Height	2,065 x 827 x 1,147 mm	Trail	104mm
Wheelbase	1,360mm	Kerb	122.6kg
		Weight	_
Seat Height	849mm	Colour	Red and White
Ground Clearance	265mm		
Fuel Tank Capacity	12 litres		







